

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture	BI-OO-CYST
Registration number	-
Synonyms	None.
Issue date	11-August-2015
Version number	02
Revision date	09-March-2017
Supersedes date	11-August-2015

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	BIOCIDAL PRODUCT - PT3: veterinary hygiene disinfectant. For professional use only.
Uses advised against	None known.

1.3. Details of the supplier of the safety data sheet

Supplier

Company name	BIOLINK Limited
Address	1 Narvik Road Sutton Fields Ind. Est. Hull, HU7 0AB
Telephone number	+ 44-(0)-1759 303 444
Fax number	-
E-mail	info@biolinklimited.co.uk
Contact	-

1.4. Emergency telephone number + 44-(0)-1759 303 444 (office hours only)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Acute toxicity, oral	Category 4	H302 - Harmful if swallowed.
Acute toxicity, dermal	Category 4	H312 - Harmful in contact with skin.
Skin corrosion/irritation	Category 1C	H314 - Causes severe skin burns and eye damage.
Skin sensitisation	Category 1	H317 - May cause an allergic skin reaction.

Hazard summary

Causes severe skin burns and eye damage. Harmful if swallowed. May cause an allergic skin reaction. Dangerous for the environment if discharged into watercourses.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: 2-Butoxyethanol, Acetic acid, Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs., P-Chloro-M-Cresol

Hazard pictograms



Signal word

Danger

Hazard statements

H302 Harmful if swallowed.

H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.

Precautionary statements

Prevention

P260 Do not breathe mist or vapour.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTRE/doctor.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage

P405 Store locked up.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information None.

2.3. Other hazards Not a PBT or vPvB substance or mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.	20 - <30	85536-14-7 287-494-3	-	-	
Classification:	Acute Tox. 4;H302, Skin Corr. 1C;H314, Aquatic Chronic 3;H412				
P- Chloro-M-Cresol	25	59-50-7 200-431-6	01-2119938953-25-XXXX	604-014-00-3	
Classification:	Acute Tox. 4;H302, Acute Tox. 4;H312, Skin Sens. 1;H317, Eye Dam. 1;H318, Aquatic Acute 1;H400				
Acetic acid	10 - <20	64-19-7 200-580-7	-	607-002-00-6	#
Classification:	Flam. Liq. 3;H226, Skin Corr. 1A;H314				
2-Butoxyethanol	10 - <20	111-76-2 203-905-0	01-2119475108-36-XXXX	603-014-00-0	#
Classification:	Flam. Liq. 3;H226, Acute Tox. 4;H302, Acute Tox. 4;H312, Skin Irrit. 2;H315, Eye Irrit. 2;H319, Acute Tox. 4;H332				

List of abbreviations and symbols that may be used above

#: This substance has been assigned Community workplace exposure limit(s).

Note B: Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: "nitric acid ...%". In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.

Composition comments The full text for all H-statements is displayed in section 16. All concentrations are in percent by weight unless otherwise indicated.

SECTION 4: First aid measures

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Call a physician or poison control centre immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control centre immediately.
Ingestion	Call a physician or poison control centre immediately. Rinse mouth. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

4.2. Most important symptoms and effects, both acute and delayed Effects on exposure by inhalation may include sore throat, cough, burning sensation, shortness of breath and labored breathing. Burning pain and severe corrosive skin damage. Irritation of nose and throat. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Ingestion may produce burns to the lips, oral cavity, upper airway, esophagus and possibly the digestive tract.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing media Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media Use of water may result in the formation of very toxic aqueous solution. Do not allow run-off from firefighting to enter drains or water courses.

5.2. Special hazards arising from the substance or mixture During fire, gases hazardous to health may be formed. Combustion products may include: carbon oxides, sulfur compounds and chlorine compounds.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not get in eyes, on skin, on clothing. Do not breathe mist or vapour. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

For emergency responders Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

6.3. Methods and material for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapours or divert vapour cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling Do not breathe mist or vapour. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities Store locked up. Store in original tightly closed container. Store away from incompatible materials (see section 10 of the SDS).

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits****UK. EH40 Workplace Exposure Limits (WELs)**

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	STEL	246 mg/m ³
	TWA	50 ppm
		123 mg/m ³
		25 ppm

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	STEL	246 mg/m ³
	TWA	50 ppm
		98 mg/m ³
Acetic acid (CAS 64-19-7)	TWA	20 ppm
		25 mg/m ³
		10 ppm

Biological limit values**UK. EH40 Biological Monitoring Guidance Values (BMGVs)**

Components	Value	Determinant	Specimen	Sampling time
2-Butoxyethanol (CAS 111-76-2)	240 mmol/mol	Butoxyacetic acid	Creatinine in urine	*

* - For sampling details, please see the source document.

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no effect levels (DNELs)**General Population**

Components	Value	Assessment factor	Notes
2-Butoxyethanol (CAS 111-76-2)			
Long-term, Systemic, Dermal	38 mg/kg	4	
Long-term, Systemic, Inhalation	49 mg/m ³		
Long-term, Systemic, Oral	3.2 mg/kg	3	
Short-term, Local, Inhalation	123 mg/m ³		
Short-term, Systemic, Dermal	44.5 mg/kg	30	
Short-term, Systemic, Inhalation	426 mg/m ³	30	
Short-term, Systemic, Oral	13.4 mg/kg	30	

Workers

Components	Value	Assessment factor	Notes
2-Butoxyethanol (CAS 111-76-2)			
Long-term, Systemic, Dermal	75 mg/kg	2	
Long-term, Systemic, Inhalation	98 mg/m ³		
Short-term, Systemic, Dermal	89 mg/kg	15	
Short-term, Systemic, Inhalation	663 mg/m ³	15	

Predicted no effect concentrations (PNECs)

Components	Value	Assessment factor	Notes
2-Butoxyethanol (CAS 111-76-2)			
Freshwater	8.8 mg/l	10	

Exposure guidelines**UK EH40 WEL: Skin designation**

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.
Individual protection measures, such as personal protective equipment	
General information	Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.
Eye/face protection	Wear approved, tight fitting indirect vented or non-vented safety goggles where splashing is probable. Face shield is recommended.
Skin protection	
- Hand protection	Wear appropriate chemical resistant gloves.
- Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.
Environmental exposure controls	Inform appropriate managerial or supervisory personnel of all environmental releases.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state	Liquid.
Form	Liquid.
Colour	Greenish-brown.
Odour	Not available.
Odour threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	> 100 °C (> 212 °F)
Flash point	> 91.0 °C (> 195.8 °F) (EEC A9)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	1.07 (OECD109)
Solubility(ies)	Completely soluble.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	525 °C (977 °F) (A15)
Decomposition temperature	Not available.
Viscosity	9.58 mPa.s at 40°C: (OEDC 114) 17.9 mPa.s at 20°C (OEDC 114)
Explosive properties	Not available.
Oxidising properties	Not available.
9.2. Other information	
Surface tension	Pure 20°C: 33.12 mN/m (EEC A5) 1% 20°C: 34.22 mN/m (EEC A5)

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidising agents. Bases.
10.6. Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. Prolonged inhalation may be harmful.
Skin contact Harmful in contact with skin. Causes severe skin burns. May cause an allergic skin reaction.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

Eye contact Causes serious eye damage.
Ingestion Causes digestive tract burns. Harmful if swallowed.

Symptoms Effects on exposure by inhalation may include sore throat, cough, burning sensation, shortness of breath and labored breathing. Burning pain and severe corrosive skin damage. Irritation of nose and throat. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Ingestion may produce burns to the lips, oral cavity, upper airway, esophagus and possibly the digestive tract.

11.1. Information on toxicological effects

Acute toxicity Harmful in contact with skin. Harmful if swallowed. May cause an allergic skin reaction.

Components	Species	Test results
Acetic acid (CAS 64-19-7)		
Acute		
Dermal		
LD50	Rabbit	1060 mg/kg
Inhalation		
LC50	Rat	11.4 mg/l, 4 Hours
Oral		
LD50	Rat	3310 mg/kg
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs. (CAS 85536-14-7)		
Acute		
Oral		
LD50	Rat	1470 mg/kg (Approximate)
P- Chloro-M-Cresol (CAS 59-50-7)		
Acute		
Dermal		
LD50	Rat	> 5000 mg/kg
Oral		
LD50	Mouse	600 mg/kg
	Rat	3636 mg/kg
Other		
LD50	Mouse	70 mg/kg
	Rat	400 mg/kg

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye irritation Causes serious eye damage.

Respiratory sensitisation Based on available data, the classification criteria are not met.

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible.

Carcinogenicity Due to partial or complete lack of data the classification is not possible.

IARC Monographs. Overall Evaluation of Carcinogenicity

2-Butoxyethanol (CAS 111-76-2)

3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity - single exposure Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity - repeated exposure Due to partial or complete lack of data the classification is not possible.

Aspiration hazard Due to partial or complete lack of data the classification is not possible.

Mixture versus substance information No information available.

Other information Not available.

SECTION 12: Ecological information

12.1. Toxicity Toxic to aquatic life.

Product		Species	Test results
BI-OO-CYST (CAS Mixture)			
Aquatic			
Algae	ErC50	Pseudokirchneriella subcapitata	32.97 mg/l, 72 Hours SOP E203 -OECD 201
			27.15 mg/l, 48 Hours SOP E203 -OECD 201
	NOEC	Pseudokirchneriella subcapitata	10 mg/l, 72 Hours SOP E203 -OECD 201
Crustacea	EC50	Daphnia	28.3 mg/l, 24 Hours OECD 202
			9.444 mg/l, 48 Hours OECD 202
	NOEC	Daphnia	9 mg/l, 24 Hours OECD 202
Acute			
Fish	LC50	Rainbow trout	2.892 mg/l, 96 Hours OECD 203

Components		Species	Test results
Acetic acid (CAS 64-19-7)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	65 mg/l, 48 hours
Fish	LC50	Bluegill (Lepomis macrochirus)	75 mg/l, 96 hours
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs. (CAS 85536-14-7)			
Aquatic			
Crustacea	LC50	Hyaella azteca	7.6 mg/l, 48 hours
Fish	LC50	Lepomis macrochirus	1.67 mg/l, 96 hours
		Naked goby (Gobiosoma bosc)	

12.2. Persistence and degradability The product is biodegradable. (OECD 301D).

12.3. Bioaccumulative potential No data available.

Partition coefficient n-octanol/water (log Kow)

2-Butoxyethanol (CAS 111-76-2)	0.83
Acetic acid (CAS 64-19-7)	-0.17
P- Chloro-M-Cresol (CAS 59-50-7)	3.1

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil This product is water soluble and may disperse in soil.

12.5. Results of PBT and vPvB assessment Not a PBT or vPvB substance or mixture.

12.6. Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

BI-OO-CYST

928954 Version #: 02 Revision date: 09-March-2017 Issue date: 11-August-2015

SDS UK

7 / 10

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.
EU waste code	Product: 07 06 03* Packaging: 15 01 10*
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR	
14.1. UN number	UN3265
14.2. UN proper shipping name	Corrosive liquid, acidic, organic, n.o.s. (Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.; Acetic acid)
14.3. Transport hazard class(es)	
Class	8
Subsidiary risk	-
Label(s)	8
Hazard No. (ADR)	80
Tunnel restriction code	E
14.4. Packing group	III
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

RID	
14.1. UN number	UN3265
14.2. UN proper shipping name	Corrosive liquid, acidic, organic, n.o.s. (Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.; Acetic acid)
14.3. Transport hazard class(es)	
Class	8
Subsidiary risk	-
Label(s)	8
14.4. Packing group	III
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

ADN	
14.1. UN number	UN3265
14.2. UN proper shipping name	Corrosive liquid, acidic, organic, n.o.s. (Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.; Acetic acid)
14.3. Transport hazard class(es)	
Class	8
Subsidiary risk	-
Label(s)	8
14.4. Packing group	III
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IATA	
14.1. UN number	UN3265
14.2. UN proper shipping name	Corrosive liquid, acidic, organic, n.o.s. (Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.; Acetic Acid)
14.3. Transport hazard class(es)	
Class	8
Subsidiary risk	-
14.4. Packing group	III
14.5. Environmental hazards	No.
ERG Code	8L
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IMDG	
14.1. UN number	UN3265

14.2. UN proper shipping name CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.; Acetic Acid)

14.3. Transport hazard class(es)

Class 8

Subsidiary risk -

14.4. Packing group III

14.5. Environmental hazards

Marine pollutant No.

EmS F-A, S-B

14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code Not established.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorisation, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Acetic acid (CAS 64-19-7)

P- Chloro-M-Cresol (CAS 59-50-7)

Other regulations

The product is classified and labelled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

National regulations

Young people under 18 years old are not allowed to work with this product according to the EU Directive 94/33/EC on the protection of young people at work. Follow national regulation for work with chemical agents.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations Not available.

References Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any H-statements not written out in full under Sections 2 to 15

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H400 Very toxic to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Training information

Follow training instructions when handling this material.

Disclaimer

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment. The information in the sheet was written based on the best knowledge and experience currently available.